

Attrition Mill Technical Parameters / Specifications

Company Name	Raymer Engineering Corporation
Product name	Attrition Mill
Material	Mild Steel / Stainless Steel
Design Type	Standard
Power	20 HP
Capacity	200 LPH
Ring Diameter	1500 mm
Speed	1440 rpm
Motor (Hp)	3-100 HP
Phase	Three Phase / Single Phase
Power Source	Electric
Voltage	220 V – 440 V
Frequency	60 Hz
Protection	Flameproof / Non FLAME PROOF
Vessel	20 Ltr to 2000 Ltr
Usage/Application	Paints, Industrial Applications
MOQ	1 PC
Packaging	As per client's requirement.

Order the products your company requires, Contact Raymer Engineering Corporation at +(91) - 9220814009 or submit Enquiry Form. For more information on any of our high quality products and Get Quotes within hours.

Note: Looking for something specific? Customisation is also available with above products. Please specify in the Enquire now page

Note: Please note that the information on this document is for illustration purposes only as information may vary with individual products, their grade and applications industries or uses and therefore cannot be guaranteed as accurate. © Copyright 2021© **Raymer Engineering Corporation** All Rights Reserved (Terms of Use). Recreation of any materials from the site is strictly prohibited without permission. **Raymer Engineering Corporation** products are sold exclusively through **Raymer Engineering Corporation** website. Use Terms | Privacy. Please contact us to discuss precise product specifications and requirements and obtain advice on which products are required to suit your exact application needs r.n.engineer@raymerengineering.com

FOR MORE INFORMATION CONTACT US :-

Address : W-87, MIDC, Phase-2, Dombivali East, Near Metro Chemical , Dist. - Thane 421204

Email : r.n.engineer@raymerengineering.com | **Phone :** +(91) - 8048543437

Mobile : +(91) - 9220814009 | **Website :** www.paintmanufacturingmachine.com

Connect With Us :    