



Raymer Engineering Corporation

+919220814009 | +918048543437

r.n.engineer@raymerengineering.com

www.paintmanufacturingmachine.com  
www.raymerengineering.com

W-87, MIDC, Phase-2, Dombivali East,  
Near Metro Chemical, Dist. - Thane 421204



## HIGH SPEED DISPERSER

The major features bought out in this machine are

|                          |  |
|--------------------------|--|
| Motor                    | Crompton / Kirloskar / Hindustan/Siemens   |
| Hydraulic System         | Hydraulic Cylinder with power pack unit  |
| S.S.Material             | AUSTENETIC SS. physically & chemically tested  |
| Hardware                 | T.V.S./G.K.W.S./TATA/ Unbrako  |
| Panel                    | Electrical control panel with on, off push buttons and motor safety devices                |
| Variable Frequency Drive | The motor will be fitted with VFD to vary the shaft speed. (OPTIONAL AS PER CLIENT'S NEED) |

| Description           | REC/HSD           | REC/HSD           | REC/HSD           | REC/HSD           | REC/HSD           | REC/HSD           | REC/HSD           |
|-----------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
|                       | 500               | 750               | 1000              | 1500              | 2000              | 2500              | 3000              |
| Shell Vol LTS         | 650               | 950               | 1250              | 1900              | 2500              | 3150              | 3750              |
| Hydraulic Lift        | 800-<br>1000mm    | 800-<br>1000mm    | 1000-<br>1250mm   | 1250-<br>1600mm   | 1500-<br>1600mm   | 1600-<br>1800mm   | 1800-<br>2000mm   |
| Power Pack with motor | Included          | Included          | Included          | Included          | Included          | Included          | Included          |
| Motor HP              | 10/15+1           | 15/20+1           | 30/40+1           | 50/60+1           | 60/75+1           | 100+1             | 120+1             |
| Agitator Tip Speed    | 20mt/s-<br>25mt/s | 20mt/s-<br>25mt/s | 20mt/s-<br>25mt/s | 20mt/s-<br>25mt/s | 20mt/s-<br>25mt/s | 20mt/s-<br>25mt/s | 20mt/s-<br>25mt/s |
| V.F.D.                | AVAILABLE         | AVAILABLE         | AVAILABLE         | AVAILABLE         | AVAILABLE         | AVAILABLE         | AVAILABLE         |

DETAILS PROVIDED ARE LIABLE TO CHANGE AS PER THE CUSTOMER NEEDS AND PRODUCT REQUIREMENTS